



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
25.07.2001 Bulletin 2001/30

(51) Int Cl.7: **G06K 13/08**

(21) Application number: **00101200.4**

(22) Date of filing: **22.01.2000**

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
 Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Zuin, Gianni**
35035 Mestrino (PD) (IT)

(74) Representative: **Kampfenkel, Klaus, Dipl.-Ing.DE)**
Blumbach, Kramer & Partner GbR
Patentanwälte
Alexandrastrasse 5
D-65187 Wiesbaden (DE)

(71) Applicant: **MOLEX INCORPORATED**
Lisle Illinois 60532 (US)

(54) **IC card connector**

(57) An IC card connector (10) is provided for connecting an IC card (20) having a terminal array. The connector includes a base member (12) having receptacle means (26) for receiving the IC card for movement between a preload position and a latched position. The base member has a plurality of electrically conductive contacts (16) for engaging the terminal array of the IC card. An ejector member (14) is movably mounted on

the base member and is engageable with the IC card for movement therewith between the preload and latched positions. A latch (34) on the base member is engageable with the IC card for locking the IC card in its latched position. A spring (18) is operatively associated between the ejector member (14) and the base member (12) for moving the ejector member and IC card back to the preload position automatically in response to releasing the latch (34).




FIG. 4

Description

Field of the Invention

[0001] This invention generally relates to the art of electrical connectors and, particularly, to an IC card connector for connecting an IC card, such as a multi media card, in an IC card reader system such as a video camera or smartphone or the like.

Background of the Invention

[0002] IC cards have been developed and contain IC's (integrated circuits) including memory circuits, such as rams (random access memories), and control circuits, such as CPUs (central processing units). A special type of IC card, called a multi media card (or "MMC") is of increasing interest and is used in small electronic devices such as videocameras, smartphones, music players and the like. Multi media cards normally include a terminal array for connection through a card reader system to the external equipment. the connector usually includes some form of IC card socket and a plurality of electrodes or contacts exposed in the socket for engaging the terminal array of the IC card. The card is inserted into and removed from the socket, and the connector contacts are resilient or comprise springy contacts for yieldably engaging the terminal array of the card when the card is inserted into the socket.

[0003] With the ever-increasing miniaturization of IC cards and their respective connectors, various problems continue to arise. For instance, the very handling of the miniature IC cards is difficult, and proper positioning of the cards in the connector presents corresponding problems when the card is inserted into and removed from the card-receiving cavity or other receptacle means of the connector. Such card connectors may have locking means for holding the IC card in a locked reading position, but such locking means often have reliability problems. Still further, it often is very difficult to grip and remove the inserted IC card from the connector. This invention is directed to solving these various problems in a multi media card connector which is reliable and simple to manufacture and assemble.

Summary of the Invention

[0004] An object, therefore, of the invention is to provide a new and improved IC card connector for connecting an IC card having a terminal array, in an IC card reader system or the like.

[0005] In the exemplary embodiment of the invention, the connector includes a base member having receptacle means for receiving the IC card for movement between a preload position and a latched position. The base member base member has a plurality of electrically conductive contacts for engaging the terminal array of the IC card. An ejector member is movably mounted on

the base member and is engageable with the IC card for movement therewith between the preload and latched positions. Latch means are provided on the base member engageable with the IC card for locking the IC card in its latched position. Biasing means are provided between the ejector member and the base member for moving the ejector member and IC card back to the preload position automatically in response to releasing the latch means.

[0006] As disclosed herein, the IC card is movable from the preload position to the latched position in an insertion direction of the card into the receptacle means. The IC card is movable in a second direction transverse of the insertion direction into engagement with the latch means. Second biasing means are provided on the base member for engaging the IC card and biasing the IC card in the second direction into engagement with the latch means. In the preferred embodiment, the biasing means is provided by a spring arm formed integral with the base member and engageable therewith.

[0007] Other features of the invention include an abutment shoulder on the ejector member engageable by a leading edge of the IC card so that the ejector member moves with the IC card from the preload position to the latched position. The latch means is formed by a latch shoulder on the base member engageable with a trailing edge of the IC card. The biasing means comprises at least one coil spring sandwiched between a portion of the base member and a portion of the ejector member.

[0008] Other objects, features and advantages of the invention will be apparent from the following detailed description taken in connection with the accompanying drawings.

Brief Description of the Drawings

[0009] The features of this invention which are believed to be novel are set forth with particularity in the appended claims. The invention, together with its objects and the advantages thereof, may be best understood by reference to the following description taken in conjunction with the accompanying drawings, in which like reference numerals identify like elements in the figures and in which:

FIGURE 1 is a perspective view of an IC card connector embodying the concepts of the invention;
FIGURE 2 is a view similar to that of Figure 1, with an IC card inserted into the connector to a preload position;
FIGURE 3 is a view similar to that of Figure 2, but with the connector mounted behind an insertion slot in a panel;
FIGURE 4 is a view similar to that of Figure 2, with the IC card and ejector member moved to a latched position;
FIGURE 5 is a view similar to that of Figure 4, but with the connector mounted behind the insertion

slot in the panel;

FIGURE 6 is a vertical section taken generally along line 6-6 in Figure 3; and

FIGURE 7 is a vertical section taken generally along line 7-7 in Figure 5.

Detailed Description of the Preferred Embodiment

[0010] Referring to the drawings in greater detail, and first to Figure 1, the invention is embodied in an IC card connector, generally designated 10, which is extremely simple and includes two basic components, namely a base member, generally designated 12, and an ejector member, generally designated 14, along with a plurality of electrically conductive contacts, generally designated 16, and a pair of coil springs 18. Either one or both of base member 12 and ejector member 14 may be unitarily molded of dielectric material such as plastic or the like. Springs 18 may be fabricated of metal material. The connector is adapted for mounting on a surface of a printed circuit board.

[0011] Figures 2, 3 and 6 show an IC card 20 inserted into connector 10 to a preload position. Figures 4, 5 and 7 show the IC card moved from the preload position to a final latched or reading position. The IC card has a leading edge 20a (Fig. 4) and a trailing edge 20b (Fig. 2). The IC card is a miniature card of conventional or known construction and includes a terminal array (not shown) on a top side 20c of the card. In the preferred embodiment, the IC card is a multi media card (or "MMC") as is used in electronic devices such as video-cameras and smartphones.

[0012] More particularly, base member 12 includes a bottom wall 22 (Fig. 1) and a pair of upstanding side walls 24 defining a receptacle means, generally designated 26, therebetween for receiving IC card 20 in a substantially linear insertion direction generally in the direction of arrow "A" (Fig. 2). The card can be inserted to a preload position as shown in Figures 2, 3 and 6. In the preload position, Figure 6 shows that leading edge 20a of IC card 20 engages an abutment shoulder 28 which depends downwardly from each of a pair of arms 30 projecting rearwardly of ejector member 14. Therefore, any further movement of the IC card in insertion direction "A" causes the ejector member to move with the card.

[0013] Referring back to Figure 1, conductive contacts 16 include cantilevered spring contact arms 16a for engaging the terminal array on top side 20c of the IC card as seen in Figure 7 when the IC card is moved to its latched position described hereinafter. Figures 6 and 7 show that the conductive contacts are generally U-shaped and include bottom arms 16b for connection to appropriate circuit traces on the printed circuit board, as by soldering. A plurality of mounting clips or "fitting nails" 32 (Fig. 1) are insert-molded in base member 12 for connection to appropriate mounting pads on the printed circuit board, as by soldering.

[0014] Springs 18 are mounted within integral cylin-

dric portions 33 of ejector member 14. The springs are longitudinally sandwiched between portions 14a of the ejector member and portions 12a of base member 12.

[0015] Figure 1 best shows that base member 12 includes a pair of latch shoulders 34 which project upwardly from bottom wall 12 at opposite sides of receptacle means 26. As will be seen hereinafter, these latch shoulders are engageable with trailing edge 20b of IC card 20. A spring arm 36 is disposed above receptacle means 26 and includes a pair of upwardly flared tabs 36a at opposite sides thereof for guiding the IC card therebeneath. Again as described hereinafter, spring arm 36 forms a biasing means for biasing the trailing edge of the IC card into engagement with latch shoulders 34.

[0016] Figures 3 and 5 show IC card connector 10 mounted behind a panel 40 which includes a slot 42 through which IC card 20 can be inserted into receptacle means 26 of the connector. The panel has a recessed area 44 spanning both sides of slot 42 and into which an operator's fingers can be inserted to grip the IC card.

[0017] The operation of IC card connector 10 now will be described. As stated above, IC card 20 is inserted into receptacle means 26 (Fig. 1) in a generally linear direction as indicated by arrow "A" (Fig. 2). This can be considered the first or insertion direction of the IC card. The card initially is inserted to a preload position shown in Figures 2, 3 and 6. In the preload position, leading edge 20a of the card engages abutment shoulders 28 of ejector member 14.

[0018] The IC card is movable from the preload position (Figs. 2, 3 and 6) to its reading or latched position shown in Figures 4, 5 and 7. As the card moves to the latched position, ejector member 14 moves therewith, cocking coil springs 18 to springload the ejector member. In addition, when the IC card moves to its fully inserted position, trailing edge 20b of the card pass latch shoulders 34, whereupon spring arm 36 biases the IC card downwardly in the direction of arrow "B" (Fig. 7), generally transversely of insertion direction "A", so that trailing edge 20b of the card latches behind shoulders 34 of the base member. In this position, contact arms 16a of conductive contacts 16 appropriately engage the terminal array on the top side of the card.

[0019] When an operator desires to remove the IC card from connector 10, the operator inserts a finger into recessed area 44 beneath the IC card and flips the trailing edge 20b of the card upwardly in the direction of arrow "C" so that the trailing edge of the card disengages from latch shoulders 34, while moving spring arm 36 upwardly therewith. Once the trailing edge of the card is disengaged from the latch shoulders, coil springs 18 are effective to bias ejector member 14 and the IC card back outwardly, opposite insertion direction "A", from the latched position to the preload position as shown in Figure 6. In other words, the springs are operative to move the ejector member and IC card back to the preload position automatically in response to releasing the latch

means provided by latch shoulders 34 engaging the trailing edge of the card.

[0020] It will be understood that the invention may be embodied in other specific forms without departing from the spirit or central characteristics thereof. The present examples and embodiments, therefore, are to be considered in all respects as illustrative and not restrictive, and the invention is not to be limited to the details given herein.

Claims

1. An IC card connector (10) for connecting an IC card (20) having a terminal array, comprising:
 - a base member (12) having receptacle means (26) for receiving the IC card for movement between a preload position and a latched position, the base member including a plurality of electrically conductive contacts (16) for engaging the terminal array of the IC card;
 - an ejector member (14) movably mounted on the base member (12) and engageable with the IC card (20) for movement therewith between said preload and latched positions;
 - latch means (34) on the base member (12) engageable with the IC card (20) for locking the IC card in its latched position; and
 - biasing means (18) operatively associated between the ejector member (14) and the base member (12) for moving the ejector member and IC card (20) back to said preload position automatically in response to releasing said latch means (34).
2. The IC card connector of claim 1, including second biasing means (36) on the base member (12) for engaging the IC card (20) and biasing the IC card into engagement with said latch means (34).
3. The IC card connector of claim 2 wherein said second biasing means (36) is integral with the base member (12).
4. The IC card connector of claim 3 wherein said second biasing means comprises a spring arm (36) unitary with the base member (12) and engageable with the IC card (20).
5. The IC card connector of claim 1 wherein said biasing means comprises at least one coil spring (18) sandwiched between a portion (12a) of the base member (12) and a portion (14a) of the ejector member (14).
6. The IC card connector of claim 1 wherein said ejector member (14) includes an abutment shoulder

(28) engageable by a leading edge (20a) of the IC card so that the ejector member moves with the IC card from the preload position to the latched position.

7. The IC card connector of claim 1 wherein said latch means comprises a latch shoulder (34) on the base member (12) engageable with a trailing edge (20b) of the IC card.
8. The IC card connector of claim 1 wherein said IC card (20) is movable from the preload position to the latched position in an insertion direction (A) of the IC card into the receptacle means (26), and the IC card is movable in a second direction (B) transversely of said insertion direction into engagement with said latch means (34).
9. The IC card connector of claim 8, including second biasing means (36) on the base member (12) for engaging the IC card (20) and biasing the IC card into engagement with said latch means (34).
10. The IC card connector of claim 8 wherein said ejector member (14) includes an abutment shoulder (28) engageable by a leading edge (20a) of the IC card so that the ejector member moves with the IC card from the preload position to the latched position.
11. The IC card connector of claim 8 wherein said latch means comprises a latch shoulder (34) on the base member (12) engageable with a trailing edge (20b) of the IC card.
12. An IC card connector (10) for connecting an IC card (20) having a terminal array, comprising:
 - a base member (12) having receptacle means (26) for receiving the IC card for movement in an insertion direction (A) between a preload position and a latched position, the base member including a plurality of electrically conductive contacts (16) for engaging the terminal array of the IC card;
 - an ejector member (14) movably mounted on the base member (12) and having an abutment shoulder (28) engageable with a leading edge (20a) of the IC card for movement therewith between said preload and latched positions;
 - at least one latch shoulder (34) on the base member (12) engageable with a trailing edge (20b) of the IC card for locking the IC card in its latched position;
 - first biasing means (36) on the base member (12) for engaging the IC card (20) and biasing the IC card in a second direction (B) transversely of said insertion direction (A) into engage-

ment with said latch shoulder (34); and
second biasing means (18) operatively associ-
ated between the ejector member (14) and the
base member (12) for moving the ejector mem- 5
ber and IC card back to said preload position
automatically in response to moving the trailing
edge (20b) of the IC card out of engagement
with said latch shoulder (34).

13. The IC card connector of claim 12 wherein said first 10
biasing means (36) is integral with the base mem-
ber (12).
14. The IC card connector of claim 13 wherein said first 15
biasing means comprises a spring arm (36) unitary
with the base member (12) and engageable with the
IC card (20).
15. The IC card connector of claim 12 wherein said sec- 20
ond biasing means comprises at least one coil
spring (18) sandwiched between a portion (12a) of
the base member (12) and a portion (14a) of the
ejector member (14).

25

30


35


40


45


50


55



















European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 00 10 1200

| DOCUMENTS CONSIDERED TO BE RELEVANT | | | |
|--|--|---|---|
| Category | Citation of document with indication, where appropriate, of relevant passages | Relevant to claim | CLASSIFICATION OF THE APPLICATION (Int.Cl.7) |
| X | US 4 743 746 A (NEUMANN GERD ET AL) 10 May 1988 (1988-05-10) * abstract; figures 2,3 * * column 3, line 16 - line 51 * | 1,2, 5-12,15 | G06K13/08 |
| X | US 5 151 847 A (RAUTENBERG PAUL-GEORG) 29 September 1992 (1992-09-29) * column 6, line 27 - column 7, line 11; figures 7-13 * | 1,5-8, 10,11 | |
| A | US 5 202 551 A (PARRER PETER ET AL) 13 April 1993 (1993-04-13) * abstract; figures 3,4 * | 1 | |
| A | US 4 931 622 A (INOUE TAKAKATSU ET AL) 5 June 1990 (1990-06-05) * column 1, line 30 - column 2, line 5; figures 1,2A-2D * | 1 | |
| A | US 5 245 169 A (NAKANO YUJI) 14 September 1993 (1993-09-14) * abstract; figures 3,4 * | 1 | |
| A | US 5 125 505 A (KUROSAKI MUTSUO) 30 June 1992 (1992-06-30) * abstract; figure 3 * | 1 | |
| A | GB 2 217 083 A (UNISYS CORP) 18 October 1989 (1989-10-18) * abstract; figures 1-4C * | 1 | TECHNICAL FIELDS SEARCHED (Int.Cl.7) G06K G11B |
| The present search report has been drawn up for all claims | | | |
| Place of search THE HAGUE | | Date of completion of the search 19 June 2000 | Examiner Jiménez, J |
| CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document | | | |

EPO FORM 1503 03/82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 00 10 1200

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

19-06-2000

| Patent document cited in search report | Publication date | Patent family member(s) | Publication date |
|---|---------------------|----------------------------|---------------------|
| US 4743746 A | 10-05-1988 | DE 3445185 A | 12-06-1986 |
| | | DE 3575485 D | 22-02-1990 |
| | | EP 0186737 A | 09-07-1986 |
| | | JP 61139895 A | 27-06-1986 |
| US 5151847 A | 29-09-1992 | DE 4010398 A | 10-10-1991 |
| | | JP 5040859 A | 19-02-1993 |
| US 5202551 A | 13-04-1993 | AT 394462 B | 10-04-1992 |
| | | AT 119790 A | 15-09-1991 |
| | | DE 59107444 D | 04-04-1996 |
| | | EP 0459584 A | 04-12-1991 |
| | | JP 1927999 C | 12-05-1995 |
| | | JP 4232585 A | 20-08-1992 |
| | | JP 6052543 B | 06-07-1994 |
| US 4931622 A | 05-06-1990 | JP 1670268 C | 12-06-1992 |
| | | JP 3037232 B | 04-06-1991 |
| | | JP 62035893 A | 16-02-1987 |
| | | CA 1238092 A | 14-06-1988 |
| | | EP 0213041 A | 04-03-1987 |
| US 5245169 A | 14-09-1993 | JP 3228460 A | 09-10-1991 |
| | | JP 3228461 A | 09-10-1991 |
| | | JP 3228462 A | 09-10-1991 |
| | | JP 2744314 B | 28-04-1998 |
| | | JP 3228463 A | 09-10-1991 |
| US 5125505 A | 30-06-1992 | KR 9700066 Y | 04-01-1997 |
| GB 2217083 A | 18-10-1989 | GB 2183875 A | 10-06-1987 |
| | | DE 3688648 A | 05-08-1993 |
| | | DE 3688648 T | 04-11-1993 |
| | | EP 0226309 A | 24-06-1987 |
| | | JP 62295263 A | 22-12-1987 |
| | | US 4914279 A | 03-04-1990 |

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82